

Supreme Quality
ItcoTM



ACCURACY IN MICRONS

AUTOFEED DRILLING cum BORING MACHINE



ACCURACY AS PER

IS-2425



ACCURACY IN MICRONS

- DRILLING
- BORING
- REAMING
- SPOT FACING

S. NO.	PARTICULARS	SIZE
1.	DRILLING CAPACITY IN STEEL	25 / 32 mm
2.	SPINDLE MORSE TAPER	MT-3 / MT-4
3.	SPINDLE TRAVEL	165 mm
4.	SPINDLE SPEED (8 Nos)	80, 150, 220, 320, 580, 950, 1420, 2080
5.	PILLAR DIAMETER	90mm
6.	DISTANCE SPINDLE TO COLUMN	240mm
7.	MAX DISTANCE SPINDLE TO TABLE	560mm
8.	MAX DISTANCE SPINDLE TO BASE	1065mm
9.	TABLE WORKING SURFACE	400 x 400mm
10.	MOTOR	2 HP, 1440rpm, 3 Phase

SALIENT FEATURES:

- HYDRAULIC AUTOFEED
- DRILLING CYCLE: RAPID FORWARD, FEED, DWELL, RAPID RETURN
- HYDRAULIC SPINDLE FEED INFINITELY VARIABLE WITHIN THE RANGE
- ASLC (APPLICATION SPECIFIC LOGIC CONTROLLER FOR AUTOMATION)
- BUILT IN COOLANT SYSTEM
- HYDRAULIC JOB CLAMPING (OPTIONAL)
- VARIABLE SPINDLE SPEEDS WITHIN THE RANGE (OPTIONAL)
- PECKING CYCLE FOR DEEP HOLE DRILLING (OPTIONAL)
- USER FRIENDLY OPERATING SYSTEM
- SINGLE SWITCH OPERATION
- DRILL BIT WEARING IS LOW



Manufactured by:

INDIAN ENGG. CORP.

S-178 Industrial Area Jalandhar - 144004
Off: 0181-2299789, Mob.: 9814465427
E-mail: itcodrill@gmail.com www.itcodrill.com

Dealer